

DATA SHEET.

SPRAY EXTRACTION MACHINE.

SX 44



REMOVE SPOTS, CLEAN SURFACES. PRODUCTIVITY INCREASES WITH EFFICIENCY.

SX 44

- ❶ The spray extraction method machine for stain removal and deep cleaning of textile floor coverings, upholstery and hard floors are very effective. Compact and easy to operate.
- ❷ The top-quality two-level suction motor sucks up dirt particles with 295 mbars of vacuum pressure. The surfaces dry thoroughly and can be used again soon.
- ❸ This model has modular construction so that emptying the tank for dirty water is easy, for thorough cleaning as well as quick and inexpensive maintenance.
- ❹ Robust construction with two separate tanks made of high density polyethylene.
- ❺ Filters and seals can be removed without tools.
- ❶ The tank for the dirty water has a transparent lid allowing inspection of loosened dirt during operation.
- ❷ The light spray extraction machine for small to medium-sized furnished surfaces.
- ❸ The spray pressure of 4 bars enables maximum cleaning performance with minimal water consumption.
- ❹ Series standard: unbreakable adapter for synthetic flooring with three jets, aluminium spray-suction lance with grip and sturdy 2.5-metre spray-suction hose.
- ❺ Further special attachments round out the standard fittings – such as the Combi floor tool for hard floors

SX 44

L x B x H	300 x 420 x 530 mm
Working width	270 mm
Spray volume	1,5 l/min
Spray pressure	4 bar
Weight	12 kg

ELECTRICAL DATA

Power max.	1570 W
Mains cable	10 m

TANK


Solution tank capacity	14 l
Recovery tank capacity	14 l

SUCTION

Low pressure max.	295 mbar
Air flow max.	45 l/s

STANDARD EQUIPMENT

Floor tool	Plastic
Tube	2,5 m



Spray extraction function